


X-Lube[®] Bushes



Inch-sized MOS2 filled Nylon — (NYLATRON[®] GS63) available ex stock


Flanged

Part Number	Inside Diameter (inches)	Outside Diameter (inches)	Length Overall (inches)	Flange Diameter (inches)	Flange Thickness (inches)
S 1B/32	1/8	7/32	3/8	1/4	1/16
S 1A	1/8	1/2	1.1/8	3/4	1/8
S 1	3/16	5/16	1/2	9/16	1/8
S 244	3/16	3/8	1/2	9/16	1/8
S 71	1/4	3/8	7/16	3/4	3/16
S 2A/6	1/4	3/8	9/16	3/4	1/16
S 217	1/4	3/8	1.1/16	3/4	1/16
S 218	1/4	3/8	1.9/16	3/4	1/16
S 2A/43	1/4	1/2	9/32	3/4	1/8
S 63	1/4	1/2	13/16	3/4	1/8
S 2	1/4	1/2	1.1/8	3/4	1/8
S 3	5/16	7/16	7/8	11/16	1/8
S 56	5/16	5/8	5/8	7/8	1/8
S 175B	3/8	1/2	1/4	3/4	1/8
S 175A	3/8	1/2	3/8	3/4	1/8
S 340	3/8	1/2	1/2	7/8	1/8
S 4	3/8	1/2	7/8	3/4	1/8
S 219	3/8	1/2	1 9/16	1	1/16
S 230	10mm	1/2	7/8	3/4	1/8
S 256	3/8	5/8	9/16	1	1/8
S 5	3/8	5/8	1.1/8	7/8	1/8
S 360	3/8	3/4	1	1	1/16
S 6	7/16	9/16	7/8	13/16	1/8
S 394	1/2	5/8	9/16	1	1/8
S 7B/47	1/2	5/8	5/8	1	1/16
S 7	1/2	5/8	7/8	1	1/8
S 7A/31	1/2	5/8	1.1/4	7/8	1/8
S 220	1/2	5/8	1.9/16	1.1/4	1/16
S 8	1/2	3/4	1.1/8	1	1/8
S 9	9/16	11/16	7/8	13/16	1/8
S 10B	5/8	3/4	7/8	1	1/8
S 10	5/8	3/4	1.1/8	1	1/8
S 10H/40	5/8	3/4	1.1/2	1.1/16	1/16
S 222	5/8	3/4	1.9/16	1.1/2	1/16
S 10G/39	5/8	3/4	3.1/2	1.1/16	1/16
S 10J/42	5/8	7/8	3/8	1.1/8	1/8
S 10E/1	5/8	7/8	5/8	1.1/8	1/8
S 10F/7	5/8	7/8	3/4	1.1/8	1/16
S 75	5/8	7/8	7/8	1	1/8
S 10A	5/8	7/8	1.1/8	1.1/8	1/8
S 10D/3	5/8	7/8	1.1/4	1.1/8	1/16
S 365	5/8	1.1/8	21mm	1.1/2	3/16
S 11	5/8	1.1/8	1.1/2	1.1/2	1/8
S 447	3/4	7/8	3/4	1.1/8	1/8
S 101	3/4	7/8	7/8	1.1/2	3/16
S 12	3/4	7/8	1.1/8	1.1/8	1/8
S 223	3/4	7/8	1.9/16	1.3/4	1/16
S 13	3/4	1	1.3/8	1.1/4	1/8
S 14	7/8	1	1.3/8	1.1/4	1/8
S 224	7/8	1	1.9/16	1.3/4	1/16
S 15	7/8	1.1/8	1.5/8	1.3/8	1/8
S 16	1	1.1/8	1.1/8	1.3/8	1/8
S 225	1	1.1/8	1.9/16	1.3/4	1/16
S 76	1	31mm	3	1.5/8	1/8
S-17	1	1.1/4	1.5/8	1.1/2	1/8
S 17B	1	1.1/4	2.1/8	2	1/8
S 18	1.1/8	1.3/8	2.1/8	1.5/8	1/8
S 19	1.1/4	1.1/2	2.1/8	1.3/4	1/8
S 20	1.3/8	1.5/8	2.1/8	1.7/8	1/8
S 21	1.1/2	1.3/4	2.1/8	2	1/8
S 21/35	1.1/2	1.3/4	1.5/8	2.3/8	1/8

Plain

Part Number	Inside Diameter (inches)	Outside Diameter (inches)	Length Overall (inches)
P 132	3/32	5/16	5/8
P 1A	1/8	1/2	1
P 1	3/16	5/16	3/8
P 2A/6	1/4	3/8	1/2
P 166	1/4	3/8	3/4
P 217	1/4	3/8	1
P 218	1/4	3/8	1.1/2
P 2	1/4	1/2	1
P 126	1/4	5/8	1
P 2B/8	1/4	3/4	11/16
P 3	5/16	7/16	3/4
P 406	3/8	1/2	3/8
P 4	3/8	1/2	3/4
P 219	3/8	1/2	1.1/2
P 5	3/8	5/8	1
P 59	3/8	1.1/4	1
P 165	1/2	5/8	1/2
P 7	1/2	5/8	3/4
P 7A/31	1/2	5/8	1.1/8
P 220	1/2	5/8	1.1/2
P 288	1/2	5/8	2
P 60	1/2	3/4	1/2
P 8	1/2	3/4	1
P 104	1/2	1	1
P 9	9/16	11/16	3/4
P 10B	5/8	3/4	3/4
P 10	5/8	3/4	1
P 222	5/8	3/4	1.1/2
P 10A	5/8	7/8	1
P 10K/49	5/8	7/8	1.1/2
P 10C/4	5/8	7/8	2
P 11	5/8	1.1/8	1.3/8
P 12	3/4	7/8	1
P 223	3/4	7/8	1.1/2
P 116	3/4	1	7/8
P 13	3/4	1	1.1/4
P 266	3/4	1	2
P 198	3/4	1.1/4	1.3/4
P 84	3/4	2.5/8	3/4
P 14	7/8	1	1.1/4
P 224	7/8	1	1.1/2
P 15	7/8	1.1/8	1.1/2
P 16	1	1.1/8	1
P 225	1	1.1/8	1.1/2
P 76	1	31mm	3
P 17	1	1.1/4	1.1/2
P 17B	1	1.1/4	2
P 17C/21	1	1.1/2	5/8
P 18	1.1/8	1.3/8	2
P 19	1.1/4	1.1/2	2
P 20/37	1.3/8	1.5/8	3/4
P 20	1.3/8	1.5/8	2
P 21	1.1/2	1.3/4	2

Millimetre-sized MOS2 filled Nylon — (NYLATRON® GS63) — available ex stock

Flanged 

Part Number	Inside Diameter mm	Outside Diameter mm	Length Overall mm	Flange Diameter mm	Flange Thickness mm
S 200M	4	8	22	10	2
S 80M	5	8	5	15	2
S 201M	5	10	22	13	2
S 202M	6	10	22	13	2
S 48M	8	12	12	16	2
S 205M	8	12	37	15	2
S 272M	8	12.5	12	18	2
S 55M	8	16	16	22	3
S 458M	10	14	28	28	2
S 260M	10	16	17	24	3
S 206M	10	16	22	20	2
S 207M	10	16	37	20	2
S 337M	12	16	6	20	2
S 338M	12	16	9	20	3
S 208M	12	16	22	20	2
S 209M	12	16	37	20	2
S 179M	12	20	23	26	3
S 299M	12	22	29	26	15
S 210M	16	20	22	26	2
S 211M	16	20	37	26	2
S 312M	20	23	25	28	2
S 212M	20	25	22	32	2
S 213M	20	25	37	32	2
S 62M	20	25	90	35	2
S 366M	23	29	22	38	5
S 313M	25	28	25	35	2
S 214M	25	30	27	40	2
S 215M	25	30	37	40	2
S 216M	30	35	37	45	2

Plain 

Part Number	Inside Diameter mm	Outside Diameter mm	Length Overall mm
P 200M	4	8	20
P 201M	5	10	20
P 202M	6	10	20
P 203M	6	10	35
P 204M	8	12	20
P 205M	8	12	35
P 392M	8	1/2"	1/2"
P 458M	10	14	26
P 206M	10	16	20
P 207M	10	16	35
P 208M	12	16	20
P 209M	12	16	35
P 86M	13	20	27
P 127M	15	18	19
P 210M	16	20	20
P 211M	16	20	35
P 341M	16	20	35
P 370M	18	25	19
P 212M	20	25	20
P 213M	20	25	35
P 61M	20	25	90
P 333M	20	27	20
P 289M	25	28	57
P 214M	25	30	25
P 215M	25	30	35
P 216M	30	35	35
P 419M	30	40	50

X-LUBE BEARINGS are injection moulded from Molybdenum Disulphide filled Nylon but are also available against firm order in materials such as Acetal and Natural Nylon.

X-LUBE BEARINGS are light weight, low maintenance, resistant to corrosion and a wide range of chemicals. These bushes can run dry or be lubricated by the surrounding medium (e.g. water, alkalis, acids etc). They are quiet running, non-contaminating and provide electrical insulation.

Additional sizes to those listed are available made to order.